Reply filed March 17, 2005

Reply to Advisory Action dated March 2, 2005

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Previously Presented) A liquid crystal display device used with a light source,

comprising:

a first substrate;

a second substrate having first and second surfaces, wherein the first surface is disposed

against the first substrate;

a non-transparent film coated on a periphery of the second surface of the second substrate

to substantially block light emitted from the light source; and

a sheet material disposed between the light source and the second substrate, wherein at

least a portion of one edge of the sheet material adjacent to the light source is not directly under

the non-transparent film.

2. (Original) The liquid crystal display device of claim 1, wherein the first substrate

comprises first and second surfaces, the second surface being disposed against the first surface of

the second substrate, wherein a non-transparent material is formed on a periphery of the second

surface of the first substrate.

3. (Original) The liquid crystal display device of claim 1, wherein a non-transparent

material is formed on a periphery of the second surface of the second substrate.

Page 2 of 8

Application No.: 09/394,379

Reply filed March 17, 2005

Reply to Advisory Action dated March 2, 2005

4. (Original) The liquid crystal display device of claim 2, wherein the non-transparent

Docket No.: 8733,088.00

material is a black matrix.

5. (Original) The liquid crystal display device of claim 1, wherein the non-transparent film

is a black film.

6. (Original) The liquid crystal display device of claim 2, wherein the non-transparent film

and the non-transparent material are partially overlapping throughout the periphery of the second

substrate.

7. (Original) The liquid crystal display device of claim 6, wherein the non-transparent

material is a black matrix.

8. (Original) The liquid crystal display device of claim 6, wherein the non-transparent film

is a black film.

Claim 9 (Canceled).

10. (Previously Presented) The liquid crystal display device of claim 1, wherein the sheet

material includes a protective sheet, a prism sheet, and a diffusion sheet.

11. (Previously Presented) The liquid crystal display device of claim 10, wherein the first

substrate comprises first and second surfaces, the second surface of the first substrate being

Page 3 of 8

Application No.: 09/394,379

Reply filed March 17, 2005

Reply to Advisory Action dated March 2, 2005

disposed against the first surface of the second substrate, wherein a non-transparent material is

Docket No.: 8733.088.00

formed on a periphery of the second surface of the first substrate.

12. (Original) The liquid crystal display device of claim 11, wherein the non-transparent film

and the non-transparent material are partially overlapping throughout the periphery of the second

substrate.

13. (Original) The liquid crystal display device of claim 12, wherein the non-transparent

material is a black matrix.

14. (Original) The liquid crystal display device of claim 12, wherein the non-transparent film

is a black film.

15. (Previously Presented) A method of manufacturing a liquid crystal display device for use

with a light source, comprising:

providing a first substrate;

providing a second substrate having first and second surfaces, wherein the first surface is

disposed against the first substrate;

coating a non-transparent film on a periphery of the second surface of the second

substrate to substantially block light emitted from the light source; and

disposing a sheet material between the light source and the second substrate, wherein at

least a portion of one edge of the sheet material adjacent to the light source is not directly under

the non-transparent film.

Page 4 of 8

Reply filed March 17, 2005

Reply to Advisory Action dated March 2, 2005

the second surface of the first substrate.

16. (Previously Presented) The method of claim 15, wherein the first substrate comprises first and second surfaces, the second surface of the first substrate being disposed against the first surface of the second substrate, wherein a non-transparent material is formed on a periphery of

- 17. (Previously Presented) The method of claim 15, wherein a non-transparent material is formed on a periphery of the first surface of the second substrate.
- 18. (Original) The method of claim 17, wherein the non-transparent material is a black matrix.
- 19. (Original) The method of claim 15, wherein the non-transparent film is a black film.
- 20. (Original) The method of claim 16, wherein the non-transparent film and the nontransparent material are partially overlapping throughout the periphery of the second substrate.
- 21. (Original) The method of claim 20, wherein the non-transparent material is a black matrix.
- 22. (Original) The method of claim 20, wherein the non-transparent film is a black film.
- 23. (Original) The method of claim 19, wherein the black film is formed by any one of a printing process and a coating process.

Reply filed March 17, 2005

Reply to Advisory Action dated March 2, 2005

24. (Previously Presented) The liquid crystal display device of claim 1, wherein the sheet

material comprises an uppermost sub-layer having a first length and at least one underlying sub-

layer arranged under the uppermost sub-layer and having a second length, wherein the first

length is substantially equal to the second length.

25. (Previously Presented) A liquid crystal display device used with a light source,

comprising:

a first substrate;

a second substrate having first and second surfaces, wherein the first surface is disposed

against the first substrate;

a non-transparent film coated on a periphery of the second surface of the second substrate

to substantially block light emitted from the light source; and

a sheet material disposed between the light source and the second substrate, wherein the

non-transparent film does not overlap at least a portion of one edge of the sheet material adjacent

to the light source.

26. (Previously Presented) A method of manufacturing a liquid crystal display device for use

with a light source, comprising:

providing a first substrate;

providing a second substrate having first and second surfaces, wherein the first surface is

disposed against the first substrate;

coating a non-transparent film on a periphery of the second surface of the second

substrate to substantially block light emitted from the light source; and

Reply filed March 17, 2005

Reply to Advisory Action dated March 2, 2005

disposing a sheet material between the light source and the second substrate, wherein the non-transparent film does not overlap at least a portion of one edge of the sheet material adjacent

to the light source.

Claim 27 (Canceled).

Claim 28 (Canceled).

29. (Previously Presented) The liquid crystal display device of claim 24, wherein one edge of

the sheet material is adjacent to the light source.

Claims 30-32 (Canceled).